





IT'S TIME TO GET CONNECTED!















S_Cal PRO

Professional calipers coolants and lubricants protected IP67. Sleeping mode after 20 minutes with automatic wake-up by moving the electronic. Position memorized in sleeping mode (Absolute system*).

Order number	Range (mm)	Resolution (mm)	Depth rod (mm)	Max Error (µm)
910.1502	150	0.01	4x1.4	20
910.1507	150	0.01	Ø 1.5	20
910.1522	200	0.01	4x1.4	30
910.1532	300	0.01	-	30



WITH MICRON RESOLUTION!



EXCELLENT 4 μm REPEATABILITY.

Order nur	nber	Range (mm)	Resolution (mm)	Depth rod (mm)	Max Error (µm)
910.95	02	150	0.001	4x1.4	15
910.97	07	150	0.001	Ø 1.5	15









810.1506

\$\$299



FROM S\$299

S_Cal EVO Bluetooth®

Professional Bluetooth® calipers coolants and lubricants protected IP67. Sleeping mode after 20 minutes with automatic wake-up by moving the electronic. Large display, customizable ergonomic button.


Order number	Range (mm)	Resolution (mm)	Depth rod (mm)	
810.1506	150	0.01	4x1.4	
810.1516	150	0.01	Ø 1.5	
810.1526	200	0.01	4x1.4	
810.1536	300	0.01	-	
981.7100	USB Dongle Bluetooth® for PC Windows / D300S			
981.7161		Software Vmux		



DIN 862



1/P67







\$\$1799



3m = 3.3 kg

ULTRA-LIGHT LONG CALIPERS

UL4

Ultimate calipers for big external and internal dimensions up to 3000 mm. Reinforced aluminium frame, big display with built-in Bluetooth® transceiver, force control system, long jaws coated with titanium.

Order number	Range (mm)	Repeatability (µm)	Мах еггог (µm)	Weight (kg)
811.1404	0-400	20	30	1.5
811.1406	0-600		40	1.6
811.1410	0-1000		50	1.9
811.1415	0-1500		90	2.3
811.1420	0-2000		120	2.6
811.1425	0-2500	30	150	2.9
811.1430	0-3000		200	3.3









UNICAL

Version without jaws of our UL4 caliper on which you can mount a wide range of accessories, for many external and internal applications.





981.7161

S\$269

Order number	Description
981.7100	USB Dongle Bluetooth® for PC Windows / D300S
981.7161	Software Vmux







\$\$499

S_Mike PRO

Professional micrometers coolants and lubricants protected IP67. Sleeping mode after 20 minutes with automatic wake-up by moving the spindle. Position memorized in sleeping mode (Absolute system*). Quick displacement of the measuring spindle 12 mm per rotation. High repeatability, the operator cannot influence the measurement result. Available in several versions with different anvils.

Order number	Range (mm)	Anvils (mm)	Repeatability (µm)
903.0300	0-30	Ø 6.5	1
903.0600	30-66	Ø 6.5	1
903.1000	66-102	Ø 6.5	1
903.1360	100-136	Ø 6.5	2
903.1600	125-161	Ø 6.5	2
903.1301	0-102 (3x instr,)	Ø 6.5	1
910.1301	1x caliper + 1x mike + micrometer stand	-	-





\$\$2050

\$\$950

ULTRA FAST SPINDLE SYSTEM!

IP67 DIN 862





S_Mike PRO Bluetooth®

Our popular quick micrometer is now available with built-in Bluetooth® transceiver.

Order number	Range (mm)	Anvils (mm)	
903.0306	0-30	Ø 6.5	
903.0606	30-66	Ø 6.5	
903.1006	66-102	Ø 6.5	
981.7100	USB Dongle Bluetooth® for PC Windows / D300S		
981.7161	Software Vmux		



S_Mike PRO Flat-Ball & Ball-Ball

Order number	Range (mm)	Anvils (mm)
903.0304	0-30	Ø 7 flat & Ø 7 spherical
903.0305	0-30	2x Ø 7



S_Mike PRO Disk

Order number	Range (mm)	Anvils (mm)
903.0303	0-30	Ø 25



S_Mike PRO Knife & Ø2mm

Order number	Range (mm)	Anvils (mm)
903.0301	0-25	Ø 2
903.0302	0-25	0.75x6.5









S\$1900



Our popular XTreme bore gauges series, available in handle or dial type. Large measuring range Ø 2-300 mm. All instruments are delivered with setting ring(s) and certificates. Coolants and lubricants protected IP65. Special heads for grooves, slots, threads, splines, etc. can be customized on request.



1P67

New version of our successful XTreme bore gauges series redesigned with larger LCD display and optional built-in Bluetooth® transceiver.

Coolants and lubricants protected IP67.





SPECIAL HEADS







*available on request.



Lifetime Warranty **SWISS**



FROM

\$\$499

Sylvac Stands for indicators


Swiss made high quality granite stands for indicators. Very rigid construction with fine adjustment of the position in height. Granite grade 00.

Order number	Dimensions (mm)	Clamping (mm)	A (mm)	B (mm)
808.1204	200x300x60	ø8	115	ø35
808.1206	100x150x40	ø8	70	ø25
808.1207	100x150x40	ø8	70	ø35
808.1203	140x240x40	ø8	70	ø35
808.1201	140x240x40	ø8	115	ø35

805.8601

\$\$1949

808.1207 \$\$570





POWERED BY STANDARD BATTERY



FROM

\$\$1499

1 NANO RESOLUTION





Long range indicators with 0.1 micron resolution. Incredible accuracy over 100 mm. Low measuring force, clamping diameter 8 mm and 25 mm.

Order number	Range (mm)	Measuring force (N)	Accuracy (µm)	Clamping (mm)	Repeatability (µm)
805.8501	25	0.75 - 1.00	1.3	ø8 h6	
805.8502	25	0.30	1.3	ø8 h6	
805.8601	50	0.75 - 1.15	1.5	ø8 h6	
805.8602	50	0.75 - 1.15	1.5	ø25 g7	0.2
805.8701	50	0.40	1.5	ø8 h6	
805.8702	50	0.40	1.5	ø25 g7	
805.8661	100	0.90 - 1.30	2.2	ø8 h6	







\$\$749



S_Dial WORK BLUETOOTH® SERIES

High quality and very robust indicators with built-in Bluetooth® transceiver bringing new solutions for data collection. Duplex transmission mode allowing to send commands from the computer or device connected Displayed values are synchronized after zero or presetting. Available in 3 different models.

Order number	Model	Range (mm)	Resolution (mm)	Мах еггог (µm)	Repeatability (µm)
805.6301	Advanced BT	12.5	0.001	3	
805.6501	Advanced BT	25	0.001	4	2
805.6621	Advanced BT	50	0.001	5	L
805.6661	Advanced BT	100	0.001	6	
805.6307	Ana. Nano BT	12.5	0.0001	1.8	
805.6507	Ana. Nano BT	25	0.0001	2.2	0.5
805.6306	Nano BT	12.5	0.0001	1.8	0.0
805.6506	Nano BT	25	0.0001	2.2	











Sylvac BT Smart App

Order number	Description	Price (SGD)
981.7100	USB Dongle Bluetooth® for PC Windows / D300S	99
981.7161	Software Vmux	269
981.7110	Software Sylconnect	499

Special Offer

PROMOTION FREE SOFTWARE!

Pack A

Buy 2x Bluetooth® indicators and get a free dongle!



Pack B

Buy 4x Bluetooth® indicators and get a free dongle and a free Sylconnect or a free Vmux!



Pack C

Buy 8x Bluetooth® indicators and get 2 free dongles and 2 free Sylconnect or 2 Vmux !







SAVE \$1196!







S_Dial Work

FROM

\$\$299

EASY TO USE, ONE BUTTON ONE FUNCTION



Order number	Range (mm)	Resolution (mm)	Мах еггог (µm)
805.1201	12.5	0.01	10
805.1301	12.5	0.001	4
805.1401	25	0.01	10
805.1501	25	0.001	5
805.1601	50	0.01	20
805.1621	50	0.001	7

S_Dial WORK Basic & Advanced

High quality and very robust digital indicators range coolants and lubricants protected. Sleeping mode after 20 minutes with automatic wake-up by moving the spindle. Position memorized in sleeping mode (Absolute system*). Function assigned to the button programmable by PC.





Functions	Basic	Advanced
Preset	_o 1)	•
Preset on Min/Max		•
Measuring direction		•
Hold		•
Min / Max / Delta		•
Tolerances		•
Absolute system*	•	•
Auto off	•	•
Multiplication factor		•
Ref I / II		•







Order number	Range (mm)	Resolution (mm)	Мах еггог (µm)
805.5201	12.5	0.01	10
805.5301	12.5	0.001	3
805.5401	25	0.01	10
805.5501	25	0.001	4
805.5601	50	0.01	20
805.5621	50	0.001	5
805.5641	100	0.01	20
805.5661	100	0.001	6
805.5671	150	0.01	20
805.5681	150	0.001	10

¹⁾ Preset configuration only by PC.











\$\$1699

4 IP65 Front face

TOUCH SCREEN 2 CHANNELS DISPLAY UNIT

COMPATIBLE WITH MOST OF THE PROBES ON THE MARKET!













Digital display units D70S/H/I

Digital display units with 4.3" touch screen interface and 2 probes input, compatible with Excel and SPC.

Available in 3 different versions:

- D70S for Sylvac capacitive probes
- D70I for Sylvac and other brands inductive probes
- D70H for incremental or 1VPP probes.

Order number	Model	Probes
804.2071	D70I	Inductive Sylvac
804.2072	D70H	incremental or 1VPP
804.2072	D70S	Capacitive Sylvac

^{*}accessories and probes not included





SOLUTIONS FOR MULTIGAUGING APPLICATIONS

D400S \$\$3500



*accessories and probes not included



Touch-screen multifunctionnal unit compatible with M-BUS system.

- up to 32 channels displayed simulteanously
- Max. 99 instruments connected

Order number	er Model Probes/Instruments	
804.2400	D400S	Connection through M-BUS modules

FROM

\$\$2999

Digital display units D3005 V2

Touch-screen multifunctionnal unit compatible with M-BUS system, USB Sylvac cables and Bluetooth instruments.

- up to 8 channels dispayed simulteanously
- Max. 32 instruments connected
- Up to 16 instruments connected by Bluetooth®

Order number	Model	Probes/Instruments	
804.1300	D300S V2	6 USB, M-BUS Bluetooth® compatible	
804.1310	D300S V2	6 USB, 2 probe input Bluetooth® compatible	
981.7100	USB Dongle Bluetooth® for PC Windows / D300S		







\$\$749

M-bus & M-bus RS modules

M-Bus: Interface modules used to connect probes and instruments from different brands to Sylvac D300S and D400S units.

M-Bus RS: Master module designed to connect M-BUS module(s) to computer without passing by display unit.

Order number	Model	Probes / Instruments	Inputs
840.2102	MB-2C	Capacitivo Sulvac	2
840.2104	MB-4C	Capacitive Sylvac	4
840.2108	MB-8i	Inductive Sylvac	8
840.2122	MB-2S	Incremental	2
840.2114	MB-4D	Digimatic	4
840.2118	MB-8D	Digimatic	8
840.2130	MB-10	PLC I/O	8
840.2160	MB-RS	M-BUS -> Computer	255

\$\$599





Sylvac Inductive probes series

S\$450

FROM

Robust and long lasting ball bearing guidance inductive probes specially designed for multi gauging applications. Excellent repeatability allowing to measure by comparison on jigs and fixtures. Available in 2 versions:

- Spring push (force given by spring)
- Pneumatic push (force given by air)

Order number	Model	Push	Travel	Мах еггог (µm)	Repeatability (µm)	Force – Standard (N)
900.1101	P2i	Spring	±2	2	0.15	0.7
900.1102	P2iP	Pneumatic	±5	2	0.15	0.85/0.4 Bar - 2/0.8 Bar
900.1111	P5i	Spring	±2	5	0.15	0.7
900.1112	P5iP	Pneumatic	±5	5	0.15	0.85/0.4 Bar - 2/0.8 Bar

*for more probes, kindly request for full catalogue





\$\$1199

EASY TO USE

FROM

Hi_Cal 150/300/450

Best seller 1D motorized height gauge specially designed to quickly measure heights, distances, internal and external diameters, centerline distances, etc.

Big display with intuitive functions. Very small base requiring only a small granite.

Order number	Range (mm)	Resolution (mm)	Ассигасу (µm)	
830.0150	150	0.001	2.5+L/175	
830.0300	300	0.001	2.5+L/175	
830.0450	450	0.001	2.5+L/175	
930.2150	Accessory kit (full)			
930.2151	Accessory kit (basic)			

FREE GIFTS Worth \$1300!



930.2150

*with purchase of Hi Cal 450

0 S

830.0450

Hi_Gage ONE 400/600

Top quality measuring and scribing instrument with heavy duty construction. Self and quick locking system of the unit with fine adjustment knob. Supplied with 840.9002.

Order number	Resolution (mm)	Range (mm)	Accuracy (µm)		
840.0400	0.01	400	40		
840.0600	0.01	600	50		
840.9001	Ball probe Ø 8mm				
840.9002	Scribing probe (standard included)				
905.2247	Clamping stem Ø 8mm				
905.4321	Test indicator short				

905.2247 840.9002 840.9001

905.4321

NEW







Sylvac Lifetime Warranty

First time ever! Confident in our Swiss quality standard, Sylvac offers a Lifetime Warranty on all S_Dial Work and S_Dial Pro Series digital indicators. To enjoy this incredible guarantee, simply register your instrument on our website within 30 days after the purchase date.

0.0000



Lifetime Warranty










www.sylvac.ch/LifetimeWarrantyRegistration





Products sold in Indonesia will be quoted in IDR at prevailing rates Images may differ from reality. Change without prior notice





Sales Agent for Singapore and Indonesia

LFC PTE. LTD.

3 Ubi Road 2, #03-01, Zervex email: sales@lfc.com.sq Web: www.lfc.com.sg

12.0 132

PT. LFC TEKNOLOGI INDONESIA

0.00

Gedung Graha Pena, Kota Batam Indonesia 29461 Tel: +62 778 464 465 email: sales@lfc.co.id Web: www.lfc.co.id

SYLVAC SA Ch. du Closalet 16 CH-1023-Crissier

+41 (0) 21 637 67 57 Fax: +41 (0) 21 637 67 40 E-mail: vente@sylvac.ch Web: www.sylvac.ch